



WOOD

Epoque 2-strip
Classic Collection

Product
Datasheet
2014

WOOD

Epoque 2-strip Classic Collection



TECHNICAL INFORMATION	EPOQUE 2-STRIP
Thickness	14 mm
Width	194 mm
Length	2532 mm
Wearlayer thickness (mm)	app. 3,5
Weight (kg/m ²)	app. 8,0
Taber Abraser/Lacquer's wear resistance* prEN 13696	
abrasion penetration Proteco Lacq.(revs)	>4000
abrasion penetration Proteco Nat.(revs)	>3500
abrasive wear (mg/100revs)	app. 3,5
Reduction of sound weighted index index "footfall" to the room below. NF EN ISO 140-8 / Acc to NF EN ISO 717-2, ΔL _w in dB with 2 mm Tarkofoam/flex II	17
Formaldehyde emission EN 13986	E1
Reaction to Fire EN 13501	D _{fl}
Thermal insulation value (RT m ² K/W)	
board only	0,101
with rag felt	0,121
with 2 mm Tarkofoam/flex II	0,141
Installation**	Floating /Glue down
Underfloor heating compatible***	Maximum floor surface temperature 27°C with self-regulating under-floor heat system.

* Data show results with new components according to 2006 update.
Method not applicable for stained, brushed or hardwax oiled products.

** Contact your flooring supplier for further information.

*** Not suitable for the woodspecies beech and maple.

Epoque Proteco Lacquer / Proteco Natura



EPOQUE 2-STRIP	Lacquer 2-lock	Natura 2-lock
2-strip, 14x2532x194 mm.		
Oak Nature	•	•
Oak Rustic brushed		•
Oak White brushed		•
Oak Java brushed		•
Ash White		•
Ash Cognac brushed		•

Wood floors, Brinell Hardness (BHN), EN1534

