Declaration of Performance

DOP-ENGELS-003-20-16058801

16058801

Product-code:

www.baksteen.nl



Steenfabriek Engels Helden B.V.

Product-type:		Floudci-code. 10036601			Steenfabriek Engels Helden B.V. Steenstraat 8 b				
	baltic amber waalformaat		5981 AE Panningen		Nederland				
			GB						
			Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: HD units for use in unprotected masonry walls, colums and partitions.	NEN EN 771-1 : 2011 A1: 2015					
			System of assessment and verification of constancy of performance of the construction product						
			Notified Body IKOB-BKB No NB 0957 performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.						
			configuration:						
			Solid brick (soft mud)	EN 771-1:2011					
			Declared performance			2011			
			Dimensions	209	x 101 x 51	mm			
			Tolerances	T2	4 x 3 x 2	mm			
			Range	R1	9 x 6 x 4	mm			
			flatness of bed faces		NPD				
			parallelism of bed faces		NPD				
			Gross dry density		1635	kg/m3			
			Net dry density		NPD	kg/m3			
			Density tolerances	D1	+/- 10	%			
			Volume of frogs		3	%			
			Group of the unit		2				
			Compressive strength *						
			perpendicular to bed faces						
			* mean		17,5				
			* normalized		12,5				
			Category		1				
			Bond strength		NPD	N/mm2			
			Thermal conductivity		0,49	W/m.K	EN 174		
			Water vapour permeability		0/100		EN 174		
			Direct airborne sound insulation		NPD				
			Freeze/thaw resistance		F2		(F2/D)		
			Water absorption		10	%	, = 2)		
			Initial rate of water absorption:	1	0 - 5,0	kg/m2.min	(IW3)		
			Active soluble salts content	* '	S2		, -/		
			Moisture movement		NPD	mm/m			
			Dangerous substances		assed	-	NL-BB		
			Reaction to fire		A1				
			The performance of the product identified is in conformity with the			I			
			declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.	,		ngels			