Declaration of Performance

DOP-ENGELS-002-17-16040401

www.baksteen.nl



16040401



			Steenfabriek Engels Helden B.V. Steenstraat 8 b			
Product-type:	inka waalformaat		5981 AE Panningen	Nederland		
			GB			
			Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: HD units for use in unprotected masonry walls, colums and partitions.	NEN EN 771-1 : 2011 A1: 20		A1: 2015
			System of assessment and verification of constancy of performance of the construction product	2+		
			Notified Body IKOB-BKB No NB 0957 performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control .			
			configuration: Solid brick (soft mud)			
			Declared performance	EN 771-1:2011		
			Dimensions	209 x 101 x 50	mm	
			Tolerances	T2 4 x 3 x 2	mm	
			Range	Rm 9 x 7 x 5	mm	
			flatness of bed faces	NPD		
			parallelism of bed faces	NPD		
			Gross dry density	1900	kg/m3	
			Net dry density	NPD	kg/m3	
			Density tolerances	D2 +/- 5	%	
			Volume of frogs	0	%	
			Group of the unit	7		
			Compressive strength *			
			perpendicular to bed faces			
			* mean	25		
			* normalized	17,5		
			Category	1,0		
			Bond strength	NPD	N/mm2	
			Thermal conductivity	0,53	W/m.K	EN 1745
			Water vapour permeability	50/100		EN 1745
			Direct airborne sound insulation	NPD		
			Freeze/thaw resistance	F2		(F2/D)
			Water absorption	10	%	(, _)
			Initial rate of water absorption:	1,0 - 5,0	kg/m2.min	(IW3)
			Active soluble salts content	1,0 - 3,0 S2		(1110)
			Moisture movement	NPD	mm/m	
			Dangerous substances	passed		NL-BBk
			Reaction to fire	A1		
			The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the	Y als		
			Signed for and on behalf of the manufacturer by:	J. Engels, COO		