

PRESTIGE

WOOD - PRODUCT DATASHEET 2021



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value)		
Ash	(BHN) EN1534	4,0
Oak		3,7
Taber Abraser/Lacquer's wear resistance		
Protoco Hardwax Oil	EN 13696	N/A
Reduction of sound weighted index	EN ISO 10140-3 /	≥17
ΔL_w in dB with 2 mm Tarkofoam/flex II	EN ISO 717-2	
Thermal insulation value (RT m ² K/W)		
board only	EN ISO	0,101
with rag felt	10456:2007	0,121
with 2 mm Tarkofoam/flex II		0,141
Thermal conductivity (W/m K)	EN 12664 / EN	0,11
	14342:2013	
Construction	3-layer with softwood core	

INSTALLATION	
Installation method	2-lock for floating or glue down
Installation instruction	Download from www.tarkett.com Contact your supplier for more details
Underfloor heating compatible	Yes
Maximum floor surface temperature 27°C with self-regulating under-floor heat system	
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²	

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting, Transition moulding, Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Hardwax Oil Refresher Hardwax Oil
See more alternatives and the complete range of accessories @ www.tarkett.com	

MAINTENANCE
These Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Prestige Protoco Hardwax Oil

98 %
98 %
Natural
Renewable

100 %
Recyclable



2-LOCK



www.realwood.eu

PRESTIGE

WOOD - PRODUCT DATASHEET 2021

DESIGN

A wooden floor that appears to be worn by the sun, wind and water. The boards have a new deep and rounded "Antique brushed" effect enhanced by a hardwax oil treatment, offering an easy and long-lasting maintenance. The 4-sided minibevels underline the character of the planks.

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (4 side)	Character	Colour	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Prestige Ash Seashell	7967018	2 200 x 162 x 14	1-strip	Proteco Hardwax Oil	Antique brushed	Minibevel	Expressive	White	1	0190-0105	3,5	6	2,14	77,04	7,9
Prestige Oak White Sand	7877046	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Antique brushed	Minibevel	Calm	White	2	0190-0105	3,5	6	2,51	87,85	7,9
	7877052	2 000 x 190 x 14	1-strip	Proteco Hardwax Oil	Antique brushed	Minibevel	Calm	White	2	0190-0105	3,5	6	2,28	79,80	7,9
Prestige Oak Driftwood	7870059	2 281 x 194 x 14	3-strip	Proteco Hardwax Oil	Antique brushed	-	Calm	Warm grey	2	0190-0105	3,5	6	2,66	93,10	7,9
Prestige Oak Sand	7870058	2 281 x 194 x 14	3-strip	Proteco Hardwax Oil	Antique brushed	-	Calm	Warm beige	2	0190-0105	3,5	6	2,66	93,10	7,9
Prestige Oak	7877048	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Antique brushed	Minibevel	Lively	Warm brown	2	0190-0105	3,5	6	2,51	87,85	7,9
Prestige Oak Granite	7877054	2 000 x 190 x 14	1-strip	Proteco Hardwax Oil	Antique brushed	Minibevel	Lively	Warm grey	2	0190-0105	3,5	6	2,28	79,80	7,9
Prestige Oak Graphite	7877055	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Antique brushed	Minibevel	Lively	Warm grey	2	0190-0105	3,5	6	2,51	87,85	7,9

Due to the nature of the material this table shows typical values.

1: Fraxinus Angustifolia, 2: Quercus Robur & Quercus Petraea



Prestige Ash Seashell



Prestige Oak White Sand



Prestige Oak Driftwood



Prestige Oak Sand



Prestige Oak



Prestige Oak Granite



Prestige Oak Graphite

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com.

Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com