

## HSSR 14.0 x 160 - 1 pc | HSS Metallborr - Valsade - DIN 338 med nedsvarvat skaft

- Ø 13,5 mm – Ø 16 mm = 10 mm skaft / Ø 16,5 mm – Ø 20 mm = 13 mm skaft.



| HSSR 14.0 x 160 - 1 pc |                                                                                                                                                                                                                                                                   |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Antal i förpackning    | 1                                                                                                                                                                                                                                                                 |
| Arbetslängd (mm)       | 108                                                                                                                                                                                                                                                               |
| Ø (mm)                 | 14.0                                                                                                                                                                                                                                                              |
| Standardutrustning     | BEST 9.6, BEST 9.6 X SUPER, BEST 12 X, BEST 12 X SUPER, BDSE 12 STX, BDSE 14 T SuperTorque, BDSE 12 T SuperTorque, BDSE 14 STX, BDSE 18 STX, SB2E 12 T SuperTorque, SB2E 14 STX, SB2E 18 STX, SBE 570 R, SBE 630 R, SBE 635 RX, SBE 630 R SuperTorque, SB2E 715 R |
| Total längd (mm)       | 160                                                                                                                                                                                                                                                               |