



## Protect BSF paint

### U Protect for fire, thermal and acoustic insulation of ventilation and smoke extraction ducts

U Protect system is designed to provide fire resistant, an easy to install, lightweight and efficient thermal and acoustic insulation solution in HVAC for circular and rectangular ventilation and smoke extraction ducts up to EI 120. Protect BSF is part of ISOVER U Protect fire resistant solution. Installation guidelines must be followed and all ISOVER U Protect components used.



**Fire resistance**



**Fast installation**



**Indoor air quality**



# Protect BSF paint



## U Protect for fire, thermal and acoustic insulation of ventilation and smoke extraction ducts

Characteristic	Symbol	Unit	Quantities and measured values	Standard
<b>Application fields</b>	-	-	Protect BSF paint is part of ISOVER U Protect fire resistant solution up to E1120 for ventilation and smoke extraction ducts	EN 1366-1 EN 1366-8
<b>Material</b>	-	-	Protect BSF viscous paint is designed to be very thick and thixotropic and is used in order to create greater dry layer thicknesses	-
<b>Behaviour in fire</b>	-	-	B2 When exposed to fire or heat, the product develops micro-porous insulating layer	DIN 4102-4
<b>Processing temperature</b>	T	°C	+ 5 to + 30 °C	-
<b>Packaging</b>	-	-	15 kg PP-bucket with lid 310 ml cartridges (12 units in box)	-
<b>Storage condition</b>	-	-	T > 0 °C to + 35 °C storage time 18 months	-
<b>Water behaviour</b>	-	-	Water resistant	-
<b>Chemical behaviour</b>	-	-	Solvent free, PH neutral, white water-based dispersion Free of Volatile Organic compounds	-
<b>Instructions of use</b>	-	-	Before use, material must be stirred well Can be diluted up to 10 % or water Application by brush, roller or spatula Surface must be clean and dry and free of dust and grease Touch dry: after 4 hours under normal conditions (20 °C, RH 50 % ) completely dry 24 - 48 hours	-
<b>Classification</b>	-	-	Classification according to Regulation (EC) No 1272/2008: Protect BSF is not classified according to CLP regulation Classification according to according to Directive 67/548/ EEC or Directive 1999/45/EC : not applicable Information concerning particular hazards for human and environmen: Protect BSF does not have to be labelled	-

[www.isover-technical-insulation.com](http://www.isover-technical-insulation.com)

*The technical information corresponds to our present state of knowledge and experience at the date of printing (see imprint). But no legal guarantee can be given, unless it has been explicitly agreed. The state of experience and knowledge is developing continuously. Please see to it that you always use the latest edition of this information. The described product applications do not take special circumstances in consideration. Please verify whether our products are appropriate for the concrete application. For further information please contact our ISOVER sales offices. We deliver only according to our terms of trade and terms of delivery.*