

INSTRUCTIONS FOR USE
PRODUCT SPECIFIC INFORMATION
ONLY ON THIS PAGE

TEGERA® 8162

Chemical protection glove, fully lined, 1,3* mm (chem-layer) latex, fully dipped, crinkled grip pattern, cotton, interlock. Cat. III, blue, approved for handling foodstuffs, oil and grease resistant, oil and grease resistant palm, waterproof, moisture resistant, bulk pack, for allround work

EN ISO 21420:2020 EN 388:2016+A1:2018 3131X

EN 407:2020 X2XXX EN ISO 374-1:2016/Type B AKLPT

EN ISO 374-5:2016 FDA compliant material

LATEX



OUTER MATERIAL SPECIFICATION Natural latex
INNER MATERIAL SPECIFICATION Cotton
SIZE RANGE (EU) 7,8,9,10,11

EU-TYPE EXAMINATION 2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

ONGOING CONFORMITY CARRIED OUT BY 0598 SGS FIMKO Oy Takomitie 8, 00380 Helsinki, Finland

UK-TYPE EXAMINATION 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 6SD, United Kingdom

EN ISO ONGOING CONFORMITY CARRIED OUT BY 0120 SGS United Kingdom Limited, Rossmore Business Park, Ellesmere Park, Cheshire, CH65 3EN, United Kingdom

UK RA 0120

EAC ONLY FOR EURASIAN ECONOMIC COMMUNITY CUSTOMS UNION MEMBERS
 ПРОДУКЦИЯ СООТВЕТСТВУЕТ ТРЕБОВАНИЯМ ТР ТС 019/2011 «О БЕЗОПАСНОСТИ СРЕДСТВ ИНДИВИДУАЛЬНОЙ ЗАЩИТЫ»
EJENDALS AB
 Limavägen 28, SE-793 32 Leksand, Sweden
 Phone +46 (0)247 360 00 | Fax +46 (0)247 360 10
 info@ejendals.com | order@ejendals.com | www.ejendals.com
 Declaration of Conformity → www.ejendals.com/conformity



TEST ACCORDING TO EN ISO 374-1:2016/ EN 374-4:2019

Tested chemical	Permeation level	Degradation %
A: METHANOL (CAS NUMBER 67-56-1)	3	9,5
K: SODIUM HYDROXIDE 40% (CAS NUMBER 1310-73-2)	6	-5,3
L: SULPHURIC ACID 96% (CAS NUMBER 7664-93-9)	3	3,4
P: HYDROGEN PEROXIDE 30% (CAS NUMBER 7722-84-1)	6	-0,2
T: FORMALDEHYDE 37% (CAS NUMBER 50-00-0)	6	-21,7

INSTRUCTIONS FOR USE - CATEGORY III
 SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION

Carefully read these instructions before using this product.

EXPLANATION OF PICTOGRAMS 0 = Below the minimum performance level for the given individual hazard X= Not submitted to the test or test method not suitable for the glove design or material
Warning! This product is designed to provide protection specified in PPE Regulation (EU) 2016/425 and PPE Regulation 2016/425 as amended and brought into UK law with the detailed levels of performance presented below. However, always remember that no item of PPE can provide full protection and caution must always be taken when exposed to hazardous chemicals or other high risk situations. The performance levels are for products in new condition and do not reflect the actual duration of protection in the workplace due to other factors influencing the performance such as temperature, abrasion, degradation, etc.

EN ISO 374-1:2016 TYPE A, B, C	Protective gloves against dangerous chemicals and microorganisms - Part 1: Terminology and performance requirements for chemical risks. EN ISO 374-1:2016. Definition of breaking strength through the glove palm (Lugm) /cm ² /min. Type A = level 2 for 6 chemicals, Type B = level 2 for 3 chemicals, Type C = level 1 for 1 chemical.	A: Methanol B: Acetone C: Acetonitril D: Dichlorometan E: Karbondioxid F: Toluen	J: n-Heptan K: Sodium hydroxide 40% L: Sulphuric acid 96% M: Nitric acid 65% N: Acetic acid 99% O: Ammoniumhydroxid 25% P: Hydrogen peroxide 30% Q: Tetrahydrofuran R: Fluorvätsyra 40% S: Ethylacetat T: Formaldehyd 37%
ABCD EFGH KJLMNOPST	Permeation level Minimum break-through (hours (min))	1 2 3 4 5 6	>10 >30 >60 >120 >240 >480

Warning: EN ISO 374-1:2016 This information does not reflect the actual duration of protection in the workplace or the differentiation between mixtures and pure chemicals. The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only and relates only to the chemical tested. It can be different if used in a mixture. It is recommended to check that the glove is suitable for the intended use since the conditions at the workplace may differ from the type test depending on temperature, abrasion and degradation. When used, protective gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, snagging, rubbing, degradation caused by chemical, etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider when choosing chemical resistant gloves. Before use, inspect the gloves for any defect or imperfections. For single use only. Degradation is the percentage change in puncture resistance measured after continuous contact with the challenge chemical. EN ISO 374-4:2019

EN ISO 374-5:2016 Protective gloves against dangerous chemicals and microorganisms - Part 5: Terminology and performance requirements for microorganism risks. Protection against bacteria and fungi - Pass
Warning: EN ISO 374-5:2016 The penetration resistance has been assessed under laboratory conditions and relates only to the tested specimen.

EN 407:2020 PROTECTIVE GLOVES AGAINST THERMAL RISKS (HEAT AND/OR FIRE)
 EN 15523-1:2015: Determination of material resistance to permeation by chemicals - Part 1: Permeation by liquid chemical under conditions of continuous contact
EN 407:2020 A: Limited flame spread
B: Contact heat
C: Convective heat
D: Radiant heat
E: Small splashes of molten metal
F: Large quantities of molten metal

PERFORMANCE (A-F)	Min. O: Max. 4
Warning: EN 407:2020 if the glove consists of separate parts which are not permanently interconnected, the performance levels and the protection only apply to the complete assembly. If the gloves have a performance level 1, 2 or X in X in burning behaviour EN 407:2020 the gloves should not come in contact with naked flame. Glove tested according to the 6.6 "small splashed of molten metal" is not suitable for welding activities. In the event of a molten metal splash the glove may not eliminate all risks of burn and the user shall leave the working place immediately and take off the glove.	

EN 388:2016 +A1:2018 A: Abrasion resistance
B: Tear resistance
C: Tear strength
D: Puncture resistance
E: Cut resistance
F: Impact Protection

SUITABLE FOR CONTACT WITH FOOD SPECIFIED IN REGULATION (EU) 10/2011 AND 1935/2004
 All gloves/sleeves that are suitable for foodstuff may not be suitable for all types of food. To know for which foodstuff the glove/sleeve may be used please see the Food declaration of conformity. Contact Ejendals for more information.

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

EN 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
Finger dexterity test Min. 1; Max. 5
FITTING AND SIZING. All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. It is not explained on the front page if the size model symbol is present, the glove is shorter than a standard glove. This is done in order to enhance the comfort for special purposes - for example fine assembly work. Only wear the products in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.
STORAGE AND TRANSPORT: Ideally stored in dry and dark condition in the original package, between +10° - -30°C.
INSPECTION BEFORE USE: Check that the glove fits over present holes, cracks, tears, colour change etc. If the product becomes damaged it will NOT provide the optimal protection and should be disposed of. Never use a damaged product. Wear (or take off) gloves one at a time. Replace gloves regularly hygienic use. The usage time should never exceed X (note that some chemicals have a shorter permeation time). For more information contact Ejendals.
SHELF LIFE: 60 months.
CARE AND MAINTENANCE: Do not use any chemicals or sharp-edged objects for cleaning the gloves. Chemical gloves are not meant to be washed.
DISPOSAL: Gloves contaminated by chemicals must be disposed of in designated containers and disposed of according to the environmental legislations.
 The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

EN 407:2020 SUOJAKÄSINEET, KUUMALTA JA TUULELTA SUOJAAVAT
 A: Rajattu leikin leviäminen
 B: Kosketuslämmönkestävyys
 C: Konvektionilämmönkestävyys
 D: Säteilämmönkestävyys
 E: Suojuus pienistä sulista metalliriskillä

EN 388:2016 +A1:2018 A: Hankauskestävyys
B: Rikkokäyttö
C: Rikkokäyttö
D: Puhkaisukestävyys
E: Puhkaisukestävyys
F: Puhkaisukestävyys

