Models: AXM Everyday use:

Starting and weighing without taring:

- 1. Place the scales on a stable foundation and on the level.
- 2. Start the scales using "ON / ZERO".
- 3. If there is information in the weight display, press "ON / ZERO".
- 4. If there is still information in the weight display, press "TARE".
- 5. Begin weighing.

Weighing with taring:

- 6. Put the container on the weighing platform and press "TARE".
- 7. Begin weighing.

Expanded display:

8. Keep "MODE" depressed for about 2 seconds and the scales will display an extra decimal.

Switching off the battery-saving function:

- 9. Keep the "TARE" key depressed while turning the scales on.
- 10. Press "TARE" until F4 is shown in the display.
- 11. Press "MODE" once. 4_oFF will be shown in the display.
- 12. Press "MODE" once more.
 - $\mathbf{0}_{\bullet}\mathbf{oFF}$ will be shown in the display. ($\mathbf{0}_{\bullet}\mathbf{oFF}$ = Continuous operation.)
- 13. Save by pressing "TARE".
- 14. Finish by pressing "ON/ZERO" to return to normal weighing.

Automatic taring:

15. Keep the tare button depressed for about 5 seconds to switch on or switch off the function.

Changing between 3000 and 6000 (7500) Divisions (only non-verified scales):

- 16. Keep the "TARE" key depressed while turning the scales on.
- 17. Press "TARE" until F3 is shown in the display.
- 18. Press "MODE" for about 5 seconds.

Capacity and division is shown in the display. (3000 Divisions.)

- 19. Press "MODE" once more for about 5 seconds.
 - Capacity and division is shown in the display. (6000 / 7500 Divisions.)
- 20. Save by pressing "TARE".
- 21. Finish by pressing "ON/ZERO" to return to normal weighing.

Cleaning and maintenance:

- 22. Clean with a soft, damp cloth and use a mild detergent if necessary.
- 23. Do not use abrasive agents, acetone thinner or alcohol for cleaning.
- 24. Check accuracy at regular intervals and calibrate if necessary.

- 25. It is preferable to have the dust cover on the scales during use.26. The scales must be placed in a horizontal position for transport and when stored for any length of time.
- 27. Remove the platform prior to transport and lengthy storage.
- 28. Store in a clean, dry area.

PL.10/11/2004